

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 2

In the Claims:

This listing of claims will replace all prior versions and listings, of claims in the application:

1. (previously presented) A method of controlling a vehicle comprising:
  - inputting an intended driving demand to a vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;
  - providing a plurality of coordinator subsystems;
  - providing at least one actuator control subsystem for each coordinator subsystem;
  - outputting actuator capabilities of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;
  - outputting coordinator capabilities of each coordinator subsystem to the vehicle motion control subsystem;
  - calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;
  - outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;
  - calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems; and
  - outputting the at least one actuator demand signal to the at least one actuator control subsystem;
  - wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand.

2. (previously presented) A method of controlling a vehicle comprising:

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 3

inputting an intended driving demand to a vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

providing a plurality of coordinator subsystems;

providing at least one actuator control subsystem for each coordinator subsystem;

outputting actuator capabilities of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;

outputting coordinator capabilities of each coordinator subsystem to the vehicle motion control subsystem;

calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;

calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

outputting the at least one actuator demand signal to the at least one actuator control subsystem;

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

receiving at least one driver input from a driver of the vehicle;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input; and

receiving at least one active input from the at least one active assist program if the at least one active assist program is in the on setting;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 4

wherein a combination of the at least one driver input and the at least one active input define the intended driving demand if the at least one active assist program is in the on setting and if the driver of the vehicle does not override the at least one active assist program; and

wherein the at least one driver input defines the intended driving demand if the at least one active assist program is in the off setting or the driver of the vehicle overrides the at least one active assist program.

3. (original) The method of controlling a vehicle of claim 2, further including:

inputting environmental data into the at least one active assist program.

4. (previously presented) A method of controlling a vehicle comprising:

inputting an intended driving demand to a vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

providing a plurality of coordinator subsystems;

providing at least one actuator control subsystem for each coordinator subsystem;

outputting actuator capabilities of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;

outputting coordinator capabilities of each coordinator subsystem to the vehicle motion control subsystem;

calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;

calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems; and

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 5

outputting the at least one actuator demand signal to the at least one actuator control subsystem;

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

wherein the plurality of coordinator subsystems include a suspension coordinator subsystem, a steering coordinator subsystem and a drive train and brakes coordinator subsystem.

5. (previously presented) A method of controlling a vehicle comprising:

inputting an intended driving demand to a vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

providing a plurality of coordinator subsystems;

providing at least one actuator control subsystem for each coordinator subsystem;

outputting actuator capabilities of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;

outputting coordinator capabilities of each coordinator subsystem to the vehicle motion control subsystem;

calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;

calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems; and

outputting the at least one actuator demand signal to the at least one actuator control subsystem;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 6

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

wherein the at least one coordinator demand signal comprises a plurality of coordinator demand signals.

6. (original) The method of controlling a vehicle of claim 1, further including:

inputting actuator state measurements into the at least one actuator control subsystem;  
wherein the actuator capabilities of the at least one actuator control subsystem are determined according to the actuator state measurements.

7. (original) The method of controlling a vehicle of claim 6, wherein:

the coordinator capabilities for the associated one of the plurality of coordinator subsystems are determined according to the actuator capabilities of the at least one actuator control subsystem outputting the actuator capabilities to the associated one of the plurality of coordinator subsystems.

8. (currently amended) A vehicle control system comprising:

a vehicle motion control subsystem having a control input and a control output, the control input communicating an intended driving demand to the vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

a plurality of coordinator subsystems, each coordinator subsystem including a coordinator input and a coordinator output, each coordinator subsystem communicating coordinator capabilities of the coordinator subsystem to the ~~system~~ control input of the vehicle motion control subsystem; and

at least one actuator control subsystem for each coordinator subsystem, each actuator control subsystem having an actuator output communicating actuator capabilities of the actuator control subsystem to the coordinator input of an associated one of the plurality of coordinator subsystems;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 7

wherein the vehicle motion control subsystem calculates at least one coordinator demand signal, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

wherein the vehicle motion control subsystem outputs the at least one coordinator demand signal to the coordinator input of at least one of the coordinator subsystems;

wherein each coordinator subsystem calculates at least one actuator demand signal, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

wherein each coordinator subsystem outputs the at least one actuator demand signal to at least one actuator control subsystem; and

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand.

9. (currently amended) A vehicle control system comprising:

a vehicle motion control subsystem having a control input and a control output, the control input communicating an intended driving demand to the vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

a plurality of coordinator subsystems, each coordinator subsystem including a coordinator input and a coordinator output, each coordinator subsystem communicating coordinator capabilities of the coordinator subsystem to the ~~system~~ control input of the vehicle motion control subsystem; and

at least one actuator control subsystem for each coordinator subsystem, each actuator control subsystem having an actuator output communicating actuator capabilities of the actuator control subsystem to the coordinator input of an associated one of the plurality of coordinator subsystems;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 8

wherein the vehicle motion control subsystem calculates at least one coordinator demand signal, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

wherein the vehicle motion control subsystem outputs the at least one coordinator demand signal to the coordinator input of at least one of the coordinator subsystems;

wherein each coordinator subsystem calculates at least one actuator demand signal, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

wherein each coordinator subsystem outputs the at least one actuator demand signal to at least one actuator control subsystem; and

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

a driver subsystem for receiving inputs from a driver of the vehicle; and

at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

wherein a combination of the ~~at least one driver input~~ inputs and the at least one active input define the intended driving demand if the at least one active assist program is in the on setting and if the driver of the vehicle does not override the at least one active assist program; and

wherein the ~~at least one driver input defines~~ inputs define the intended driving demand if the at least one active assist program is in the off setting or the driver of the vehicle overrides the at least one active assist program.

10. (original) The vehicle control system of claim 9, wherein:

the at least one active assist program receives environmental data.



Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 9

11. (currently amended) A vehicle control system comprising:

a vehicle motion control subsystem having a control input and a control output, the control input communicating an intended driving demand to the vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

a plurality of coordinator subsystems, each coordinator subsystem including a coordinator input and a coordinator output, each coordinator subsystem communicating coordinator capabilities of the coordinator subsystem to the ~~system~~ control input of the vehicle motion control subsystem; and

at least one actuator control subsystem for each coordinator subsystem, each actuator control subsystem having an actuator output communicating actuator capabilities of the actuator control subsystem to the coordinator input of an associated one of the plurality of coordinator subsystems;

wherein the vehicle motion control subsystem calculates at least one coordinator demand signal, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

wherein the vehicle motion control subsystem outputs the at least one coordinator demand signal to the coordinator input of at least one of the coordinator subsystems;

wherein each coordinator subsystem calculates at least one actuator demand signal, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

wherein each coordinator subsystem outputs the at least one actuator demand signal to at least one actuator control subsystem;

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 10

wherein the plurality of coordinator subsystems include a suspension coordinator subsystem, a steering coordinator subsystem and a drive train and brakes coordinator subsystem.

12. (currently amended) A vehicle control system comprising:

a vehicle motion control subsystem having a control input and a control output, the control input communicating an intended driving demand to the vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

a plurality of coordinator subsystems, each coordinator subsystem including a coordinator input and a coordinator output, each coordinator subsystem communicating coordinator capabilities of the coordinator subsystem to the system control input of the vehicle motion control subsystem; and

at least one actuator control subsystem for each coordinator subsystem, each actuator control subsystem having an actuator output communicating actuator capabilities of the actuator control subsystem to the coordinator input of an associated one of the plurality of coordinator subsystems;

wherein the vehicle motion control subsystem calculates at least one coordinator demand signal, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

wherein the vehicle motion control subsystem outputs the at least one coordinator demand signal to the coordinator input of at least one of the coordinator subsystems;

wherein each coordinator subsystem calculates at least one actuator demand signal, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

wherein each coordinator subsystem outputs the at least one actuator demand signal to at least one actuator control subsystem;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 11

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand; and

wherein the at least one coordinator demand signal comprises a plurality of coordinator demand signals.

13. (original) The vehicle control system of claim 8, wherein:

actuator state measurements are input into the at least one actuator control subsystem; and

the actuator capabilities of the at least one actuator control subsystem are determined according to the actuator state measurements.

14. (original) The vehicle control system of claim 13, wherein:

the coordinator capabilities for the associated one of the plurality of coordinator subsystems are determined according to the actuator capabilities of the at least one actuator control subsystem outputting the actuator capabilities to the associated one of the plurality of coordinator subsystems.

15. (original) A method of controlling a vehicle comprising:

receiving at least one driver input from a driver of the vehicle;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

inputting an intended driving demand for implementing a vehicle behavior modification into a vehicle motion control subsystem;

providing an implementation subsystem; and

outputting at least a portion of the intended driving demand from the vehicle motion control subsystem to the implementation subsystem;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 12

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input.

16. (currently amended) A method of controlling a vehicle comprising:

receiving at least one driver input from a driver of the vehicle;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

inputting an intended driving demand for implementing a vehicle behavior modification into a vehicle motion control subsystem;

providing an implementation subsystem; and

outputting at least a portion of the intended driving demand from the vehicle motion control subsystem to the implementation subsystem;

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input;

wherein the implementation subsystem includes a plurality of coordinator subsystems and at least one actuator control subsystem for each coordinator subsystem; and

further including the steps of:

outputting actuator capabilities of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;

outputting coordinator capabilities of each coordinator subsystem to the vehicle motion control subsystem;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 13

calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the coordinator capabilities and the intended driving demand;

the step of outputting at least a portion of the intended driving demand includes outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;

calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the actuator capabilities and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystem; and

outputting the at least one actuator demand signal to the at least one actuator control subsystem;

wherein the at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand.

17. (original) The method of controlling a vehicle of claim 16, further including:  
inputting actuator state measurements into the at least one actuator control subsystem;  
wherein the actuator capabilities of the at least one actuator control subsystem are determined according to the actuator state measurements.

18. (original) The method of controlling a vehicle of claim 17, wherein:  
the coordinator capabilities for the associated one of the plurality of coordinator subsystems are determined according to the actuator capabilities of the at least one actuator control subsystem outputting the actuator capabilities to the associated one of the plurality of coordinator subsystems.

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 14

19. (original) The method of controlling a vehicle of claim 16, wherein:  
the plurality of coordinator subsystems include a suspension coordinator subsystem, a steering coordinator subsystem and a drive train and brakes coordinator subsystem.

20. (original) The method of controlling a vehicle of claim 16, further including:  
the at least one coordinator demand signal comprises a plurality of coordinator demand signals.

21. (previously presented) A method of controlling a vehicle comprising:  
inputting an intended driving demand to a vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;  
providing a plurality of coordinator subsystems;  
providing at least one actuator control subsystem for each coordinator subsystem;  
outputting information concerning actuator limitations of the at least one actuator control subsystem to an associated one of the plurality of coordinator subsystems;  
outputting information concerning coordinator limitations of each coordinator subsystem to the vehicle motion control subsystem;  
calculating at least one coordinator demand signal with the vehicle motion control subsystem, the at least one coordinator demand signal being determined according to the information concerning coordinator limitations and the intended driving demand;  
outputting the at least one coordinator demand signal to at least one of the coordinator subsystems;  
calculating at least one actuator demand signal with each of the at least one of the coordinator subsystems, the at least one actuator demand signal being determined according to the information concerning actuator limitations and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems; and  
outputting the at least one actuator demand signal to the at least one actuator control subsystem;

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 15

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand.

22. (previously presented) A vehicle control system comprising:

a vehicle motion control subsystem having a control input and a control output, the control input communicating an intended driving demand to the vehicle motion control subsystem, the intended driving demand requesting a vehicle behavior modification;

a plurality of coordinator subsystems, each coordinator subsystem including a coordinator input and a coordinator output, each coordinator subsystem communicating information concerning coordinator limitations of the coordinator subsystem to the system input of the vehicle motion control subsystem; and

at least one actuator control subsystem for each coordinator subsystem, each actuator control subsystem having an actuator output communicating actuator information concerning limitations of the actuator control subsystem to the coordinator input of an associated one of the plurality of coordinator subsystems;

wherein the vehicle motion control subsystem calculates at least one coordinator demand signal, the at least one coordinator demand signal being determined according to the coordinator information concerning limitations and the intended driving demand;

wherein the vehicle motion control subsystem outputs the at least one coordinator demand signal to the coordinator input of at least one of the coordinator subsystems;

wherein each coordinator subsystem calculates at least one actuator demand signal, the at least one actuator demand signal being determined according to the actuator information concerning limitations and the at least one coordinator demand signal outputted to the at least one of the coordinator subsystems;

wherein each coordinator subsystem outputs the at least one actuator demand signal to at least one actuator control subsystem; and

Applicants : Erik Coelingh et al.  
Appln. No. : 10/063,953  
Page : 16

wherein a combination of each at least one actuator demand signal provides directions for the at least one actuator control subsystem to perform the vehicle behavior modification of the intended driving demand.